

Table 1. Complete Results from the 2008 Drill Program on the North Bullfrog Property*

Hole	From ft	To ft	Int ft	opt Au	From m	To m	Int m	g/t Au
NB-08-07 Mayflower	145	170	25	0.023	44.20	51.82	7.62	0.80
	195	210	15	0.009	59.44	64.01	4.57	0.31
	235	255	20	0.009	71.63	77.72	6.09	0.32
	300	315	15	0.012	91.44	96.01	4.57	0.41
NB-08-08 Mayflower	140	145	5	0.009	42.67	44.20	1.53	0.32
	255	265	10	0.013	77.72	80.77	3.05	0.44
	335	340	5	0.015	102.11	103.63	1.52	0.53
	380	390	10	0.012	115.82	118.87	3.05	0.395
	395	410	15	0.010	120.40	124.97	4.57	0.34
	470	475	5	0.011	143.26	144.78	1.52	0.37
NB-08-09 Mayflower	315	320	5	0.070	96.01	97.54	1.53	2.40
	330	340	10	0.021	100.58	103.63	3.05	0.73
	355	365	10	0.012	108.20	111.25	3.05	0.43
	370	390	20	0.017	112.78	118.87	6.09	0.58
NB-08-10 Mayflower <i>including</i> <i>including</i>	175	180	5	0.022	53.34	54.86	1.52	0.75
	215	385	170	0.059	65.53	117.35	51.82	2.02
	275	305	30	0.209	83.82	92.96	9.14	7.18
	275	280	5	0.668	83.82	85.34	1.52	22.90
	535	540	5	0.011	163.07	164.59	1.52	0.38
NB-08-11 Mayflower * * * * *	30	40	10	0.011	9.14	12.19	3.05	0.36
	55	60	5	0.011	16.76	18.29	1.53	0.37
	65	80	15	0.010	19.81	24.38	4.57	0.35
	290	295	5	0.008	88.39	89.92	1.53	0.26
	350	360	10	0.036	106.68	109.73	3.05	1.24
	365	400	35	0.027	111.25	121.92	10.67	0.91
	405	410	5	0.015	123.44	124.97	1.53	0.51
	414	425	11	0.021	126.19	129.54	3.35	0.72
	430	450	20	0.023	131.06	137.16	6.10	0.79
	NB-08-12 Mayflower <i>including</i> <i>including</i>	135	145	10	0.009	41.15	44.20	3.05
160		170	10	0.008	48.77	51.82	3.05	0.29
175		180	5	0.016	53.34	54.86	1.52	0.55
195		205	10	0.012	59.44	62.48	3.04	0.39
230		240	10	0.056	70.10	73.15	3.05	1.90
250		255	5	0.008	76.20	77.72	1.52	0.26
265		270	5	0.009	80.77	82.30	1.53	0.31
275		370	95	0.052	83.82	112.78	28.96	1.79
290		340	50	0.084	88.39	103.63	15.24	2.87
320		325	5	0.414	97.54	99.06	1.52	14.20
375	390	15	0.009	114.30	118.87	4.57	0.31	
NB-08-13 Mayflower	0	5	5	0.038	0.00	1.52	1.52	1.30
	10	30	20	0.012	3.05	9.14	6.09	0.43
	900	905	5	0.022	274.32	275.84	1.52	0.77
NB-08-14 Mayflower	390	395	5	0.011	118.87	120.40	1.53	0.37
	515	555	40	0.031	156.97	169.16	12.19	1.06
	585	670	85	0.022	178.31	204.22	25.91	0.75
	695	700	5	0.012	211.84	213.36	1.52	0.40
NB-08-15 Mayflower	255	335	80	0.025	77.72	102.11	24.39	0.87
	340	345	5	0.008	103.63	105.16	1.52	0.29
	425	430	5	0.008	129.54	131.06	1.52	0.26
	700	705	5	0.018	213.36	214.88	1.52	0.62
	865	870	5	0.011	263.65	265.18	1.53	0.38
	940	950	10	0.011	286.51	289.56	3.05	0.39
	990	995	5	0.008	301.75	303.28	1.53	0.26
NB-08-16 Mayflower *	130	140	10	0.008	39.62	42.67	3.05	0.28
	145	155	10	0.009	44.20	47.24	3.04	0.30
	205	215	10	0.017	62.48	65.53	3.05	0.58
	225	230	5	0.008	68.58	70.10	1.52	0.28
	260	265	5	0.012	79.25	80.77	1.52	0.40

Hole	From ft	To ft	Int ft	opt Au	From m	To m	Int m	g/t Au	
	325	340	15	0.045	99.06	103.63	4.57	1.53	
NB-08-17 Mayflower	130	135	5	0.009	39.62	41.15	1.53	0.31	
	160	165	5	0.010	48.77	50.29	1.52	0.34	
	170	175	5	0.008	51.82	53.34	1.52	0.29	
	195	200	5	0.010	59.44	60.96	1.52	0.35	
	205	220	15	0.013	62.48	67.06	4.58	0.44	
	245	260	15	0.010	74.68	79.25	4.57	0.35	
	265	270	5	0.008	80.77	82.30	1.53	0.29	
	<i>including</i>	280	325	45	0.026	85.34	99.06	13.72	0.90
		300	315	15	0.055	91.44	96.01	4.57	1.90
	360	365	5	0.013	109.73	111.25	1.52	0.43	
	370	380	10	0.014	112.78	115.82	3.04	0.47	
NB-08-18 Mayflower	255	265	10	0.021	77.72	80.77	3.05	0.73	
	295	335	40	0.034	89.92	102.11	12.19	1.16	
	355	360	5	0.010	108.20	109.73	1.53	0.34	
NB-08-19 AT Hill	130	135	5	0.008	39.62	41.15	1.53	0.28	
	185	190	5	0.008	56.39	57.91	1.52	0.29	
	355	360	5	0.041	108.20	109.73	1.53	1.42	
	370	375	5	0.014	112.78	114.30	1.52	0.49	
	445	455	10	0.014	135.64	138.68	3.04	0.49	
	475	480	5	0.014	144.78	146.30	1.52	0.47	
	485	490	5	0.016	147.83	149.35	1.52	0.55	
NB-08-20 AT Hill	295	305	10	0.021	89.92	92.96	3.04	0.71	
NB-08-21 AT Hill	0	5	5	0.008	0.00	1.52	1.52	0.29	
	60	70	10	0.013	18.29	21.34	3.05	0.44	
	75	145	70	0.034	22.86	44.20	21.34	1.16	
	120	125	5	0.096	36.58	38.10	1.52	3.28	
	405	410	5	0.014	123.44	124.97	1.53	0.47	
	460	470	10	0.017	140.21	143.26	3.05	0.59	
	485	490	5	0.015	147.83	149.35	1.52	0.53	
	500	515	15	0.016	152.40	156.97	4.57	0.55	
NB-08-22 AT Hill	0	15	15	0.017	0.00	4.57	4.57	0.59	
	150	160	10	0.010	45.72	48.77	3.05	0.34	
NB-08-23 AT Hill	5	40	35	0.015	1.52	12.19	10.67	0.50	
NB-08-24 AT Hill	no values \geq 0.250 g/t								
NB-08-25 AT Hill	370	375	5	0.014	112.78	114.30	1.52	0.48	
	510	540	30	0.015	155.45	164.59	9.14	0.50	
NB-08-26 AT Hill	25	55	30	0.035	7.62	16.76	9.14	1.20	
	285	290	5	0.014	86.87	88.39	1.52	0.47	
	295	310	15	0.009	89.92	94.49	4.57	0.32	
	345	350	5	0.007	105.16	106.68	1.52	0.25	
	685	690	5	0.015	208.79	210.31	1.52	0.53	
	700	705	5	0.011	213.36	214.88	1.52	0.36	
	780	785	5	0.007	237.74	239.27	1.53	0.25	
	815	845	30	0.015	248.41	257.56	9.15	0.53	
	890	895	5	0.010	271.27	272.80	1.53	0.34	
	910	920	10	0.012	277.37	280.42	3.05	0.41	
995	1000	5	0.009	303.28	304.80	1.52	0.30		
NB-08-27 AT Hill	270	275	5	0.007	82.30	83.82	1.52	0.25	
	295	315	20	0.013	89.92	96.01	6.09	0.44	
	320	325	5	0.009	97.54	99.06	1.52	0.30	
	355	360	5	0.007	108.20	109.73	1.53	0.25	
	375	380	5	0.008	114.30	115.82	1.52	0.28	
	385	440	55	0.012	117.35	134.11	16.76	0.41	
	445	450	5	0.013	135.64	137.16	1.52	0.45	
495	505	10	0.009	150.88	153.92	3.04	0.31		
NB-08-28	980	985	5	0.011	298.70	300.23	1.53	0.37	

Hole	From ft	To ft	Int ft	opt Au	From m	To m	Int m	g/t Au
AT Hill								
NB-08-29 AT Hill	0	30	30	0.024	0.00	9.14	9.14	0.82
	35	40	5	0.008	10.67	12.19	1.52	0.26
	130	135	5	0.008	39.62	41.15	1.53	0.27
	200	205	5	0.019	60.96	62.48	1.52	0.64
	210	225	15	0.011	64.01	68.58	4.57	0.39
	255	260	5	0.008	77.72	79.25	1.53	0.26
	270	280	10	0.007	82.30	85.34	3.04	0.25
	310	325	15	0.010	94.49	99.06	4.57	0.35
	330	335	5	0.008	100.58	102.11	1.52	0.27
	350	380	30	0.010	106.68	115.82	9.14	0.34
	385	415	30	0.009	117.35	126.49	9.14	0.31
	425	430	5	0.008	129.54	131.06	1.52	0.26
	620	625	5	0.017	188.98	190.50	1.52	0.57
NB-08-30 Mayflower	295	305	10	0.014	89.92	92.96	3.04	0.48
	310	320	10	0.008	94.49	97.54	3.05	0.28
	430	435	5	0.009	131.06	132.59	1.53	0.31
	480	510	30	0.014	146.30	155.45	9.15	0.49
	570	575	5	0.010	173.74	175.26	1.52	0.33
	590	595	5	0.008	179.83	181.36	1.53	0.27
NB-08-31 Mayflower	475	480	5	0.008	144.78	146.30	1.52	0.28
	500	505	5	0.008	152.40	153.92	1.52	0.26
NB-08-32 Mayflower	no values \geq 0.250 g/t							
NB-08-33 Mayflower	no values \geq 0.250 g/t							
NB-08-34 Mayflower	no values \geq 0.250 g/t							
NB-08-35 Mayflower	125	135	10	0.008	38.10	41.15	3.05	0.29
	195	210	15	0.012	59.44	64.01	4.57	0.42
	215	220	5	0.007	65.53	67.06	1.53	0.25
	225	235	10	0.015	68.58	71.63	3.05	0.51
*	240	285	45	0.018	73.15	86.87	13.72	0.60
*	290	295	5	0.027	88.39	89.92	1.53	0.94
*	300	330	30	0.037	91.44	100.58	9.14	1.25
	355	360	5	0.010	108.20	109.73	1.53	0.35
	390	425	35	0.011	118.87	129.54	10.67	0.38
NB-08-36 Mayflower	50	70	20	0.014	15.24	21.34	6.10	0.48
	255	270	15	0.018	77.72	82.30	4.58	0.62
	285	435	150	0.027	86.87	132.59	45.72	0.92
<i>including</i>	345	370	25	0.054	105.16	112.78	7.62	1.84
	445	455	10	0.011	135.64	138.68	3.04	0.39
	465	470	5	0.008	141.73	143.26	1.53	0.29
NB-08-37 Mayflower	195	200	5	0.007	59.44	60.96	1.52	0.25
	225	235	10	0.010	68.58	71.63	3.05	0.33
	240	250	10	0.010	73.15	76.20	3.05	0.34
NB-08-38 <i>including</i> Mayflower	200	225	25	0.045	60.96	68.58	7.62	1.55
	200	210	10	0.092	60.96	64.01	3.05	3.14
	240	280	40	0.062	73.15	85.34	12.19	2.13
	260	275	15	0.142	79.25	83.82	4.57	4.86
	375	420	45	0.017	114.30	128.02	13.72	0.60
NB-08-39 Mayflower	105	110	5	0.008	32.00	33.53	1.53	0.27
	230	235	5	0.008	70.10	71.63	1.53	0.29
	250	255	5	0.008	76.20	77.72	1.52	0.28
	270	280	10	0.009	82.30	85.34	3.04	0.32
	370	380	10	0.018	112.78	115.82	3.04	0.63
NB-08-40 Mayflower	120	125	5	0.030	36.58	38.10	1.52	1.02
	195	200	5	0.008	59.44	60.96	1.52	0.26
*	225	230	5	0.009	68.58	70.10	1.52	0.31
*	235	340	105	0.024	71.63	103.63	32.00	0.81

Hole	From ft	To ft	Int ft	opt Au	From m	To m	Int m	g/t Au
<i>including</i>	270	285	15	0.075	82.30	86.87	4.57	2.56
	355	375	20	0.011	108.20	114.30	6.10	0.37
	380	390	10	0.014	115.82	118.87	3.05	0.48
	395	410	15	0.012	120.40	124.97	4.57	0.41
NB-08-41	70	75	5	0.007	21.34	22.86	1.52	0.25
Mayflower	80	85	5	0.012	24.38	25.91	1.53	0.41
	235	245	10	0.008	71.63	74.68	3.05	0.29
*	340	345	5	0.008	103.63	105.16	1.53	0.28
*	360	365	5	0.023	109.73	111.25	1.52	0.80
	370	375	5	0.007	112.78	114.30	1.52	0.25
	380	385	5	0.009	115.82	117.35	1.53	0.31
	400	460	60	0.012	121.92	140.21	18.29	0.42
	465	470	5	0.007	141.73	143.26	1.53	0.25
	495	505	10	0.008	150.88	153.92	3.04	0.28
	705	710	5	0.022	214.88	216.41	1.53	0.75

* Strict 250 ppb (0.25 g/t) cutoff with no internal waste; intervals marked with an * are bounded by intervals of no sample due to poor recovery or underground workings.